

DESCRIPTION

MODEL NUMBER: E-758-J-332	BALLAST TYPE: Electronic	STARTING METHOD: Instant Start	NUMBER OF LAMPS – LAMP TYPE: 3-F32T8, F32T8/U, F25T8, F17T8
-------------------------------------	-----------------------------	-----------------------------------	--

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE: 347 V~ ±10%	LAMP WATTS: 17/25/32 w	INPUT POWER: 87 w	INPUT CURRENT: 0.26 A	OCV: 650 v	POWER FACTOR: > 0.97	FREQUENCY: 60 Hz	SOUND RATED: A
MIN START TEMP: 32°F / 0°C	CLASS: P	TYPE: 1 outdoor	BALLAST FACTOR: 0.92	BEF: 1.06	LAMP CONNECTION: Parallel	THD (1): < 20%	NO PCB'S

(1) FOR 3-F32T8

PHYSICAL CHARACTERISTICS


CASE DIMENSIONS							
UNITS	M1	M2	M3	W	L	H	
INCHES	1.68	8.90	8.34	2.37	9.50	1.50	
TOL(+/-)	0.01	0.01	0.01	0.05	0.05	0.05	
MM	43	226	212	60	241	38	
TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30	
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	BLUE	BLUE	
INCHES	22	22	46	26	26	26	
TOL(+/-)	3/8	3/8	3/8	3/8	3/8	3/8	
MM	559	559	1168	660	660	660	
TOL(+/-)	10	10	10	10	10	10	

CARTON CHARACTERISTICS


UNITS/CARTON 10	CARTONS/LAYER 12	# OF LAYERS 8	UNITS/PALLET 960	PIECE WEIGHT 2.5 lbs	CARTON WEIGHT 26 lbs	PALLET WEIGHT 2,573 lbs
CARTONS/PALLET 96	CARTON DIMENSIONS 12" x 12" x 4"	PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 40"			

MISC.


CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.



SOLA CANADA
LIGHTING & POWER

171 Ambassador Drive
Units 8 & 9
Mississauga, ON
L5T 2J1

Phone: 905-670-0746
Fax: 905-670-9689
www.solacanada.com