

DESCRIPTION

CATALOG: E620-F-140-TP-LST	STARTING METHOD: Rapid Start	INPUT VOLTAGE: 120 V~	OCV: 275 V~	FREQUENCY: 60 Hz	
BALLAST TYPE: Magnetic Ballast	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: A	NO PCB'S

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
F40T12	1	40	0/-18	57	0.52	0.94	1.647	0.93	15	1.7
F40T12/ES	1	34	60/16	50	0.45	0.89	1.780	0.92	19	1.8
F30T12	1	30	0/-18	50	0.44	0.93	1.860	0.94	18	1.7

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	H	
	INCHES	1.687	8.906	8.344	2.375	9.5	1.5
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
	MM	43	226	212	60	241	38
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	22	22	12	12			
TOL(+/-)	3/8	3/8	3/8	3/8			
MM	559	559	305	305			
TOL(+/-)	10	10	10	10			

CARTON CHARACTERISTICS


UNITS/CARTON 10	CARTON/LAYER 12	# OF LAYERS 5	UNITS PALLET 600	PIECE WEIGHT 3.5 lbs	CARTON WEIGHT 36 lbs	PALLET WEIGHT 2 195 lbs
CARTON PALLET 60	CARTON DIMENSIONS 12" x 12" x 4"		PALLET DIMENSIONS 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 27"	

MISC.

CARTON LABEL	ELECTRICAL DIAGRAM
--------------	--------------------



PRODUCT LABEL



Certificate No. 006281

SOLA CANADA LIGHTING & POWER

171 Ambassador Drive
Units 8 & 9
Mississauga, ON
L5T 2J1

Phone: 905-670-0746
Fax: 905-670-9689

www.solacanada.com

Made in Mexico by Industrias Sola Basic S.A. de C.V.